


Product

KRS 1560L-4



KRS-1560L-4 is a crimping tool for Solar connectors like MC4[™] and similar connectors, Ø 4 mm/.157", with openbarrel conductor crimp 1.5 - 2.5, 4.0, 6.0 mm²/AWG 16 - 14, 12, 10. This tool also exist in versions for MC3™ and SOLARLOK™ connectors. (MC3™ and MC4™ are trademarks owned by Multi-Holding AG, Switzerland. SOLARLOK™ is a trademark owned by TE Connectivity, USA)



- Unique mechanism significantly reduces hand force requirement over competing crimping tools
- Versatile and easy to customize for right hand or left hand users.
- · Non-slip pad holds tool in place when leveraging on a work surface
- · Full cycle crimp mechanism to ensure consistent, reliable crimp
- · Ratchet release mechanism to clear miscrimps and obstructions
- · Precision eccentric adjustment for consistent performance and ability to calibrate
- · Hole in handle allows attachment of safety strap
- · Each tool has a unique serial number for traceability





Die profile

Crimp profile

TECHNICAL DATA Length: 256 mm/10.08" Width: 22 mm/0.87" Height: 80 mm/3.15" Weight: 642 gr/1.42 lb

Wire size: 1.5-6 mm² / AWG 16-

Crimp dimensions mm/mm²: 1,5 - 2,5 mm²/4 mm²/6 mm² Crimp dimensions inch/AWG: AWG 16 - 14/AWG 12/AWG 10 Connector: Uninsulated open barrel

connectors

Description: For Solar connectors like MC4TM and similar connectors, Ø

4 mm/ 157 inch

Life span, cycles: 50,000