

DRB 0115



DRB-0115 is a crimping tool for non insulated open barrel connectors, 2.8 + 4.8 mm, 0.1 - 1.5 mm²/.110" + .187", AWG 26-16, B/F-Crimp.

- High strength, through hardened alloy steel construction
- Versatile and easy to customize for right hand or left hand users
- Full cycle crimp mechanism to ensure consistent, reliable crimp
- Ratchet release mechanism to clear miscrimps and obstructions
- Precision eccentric adjustment for consistent performance and ability to calibrate
- · Each tool has a unique serial number for traceability

Die profile



Crimp profile

TECHNICAL DATA

 $\label{eq:logith} \begin{array}{l} \mbox{Length: 198 mm/7.8"} \\ \mbox{Width: 18 mm/0.71"} \\ \mbox{Height: 59 mm/2.32"} \\ \mbox{Weight: 350 gr0.77 lb} \\ \mbox{Wire size: } 0.1-1.5 mm^2 / AWG 26-16 \\ \mbox{Crimp dimensions mm/mm2:} \\ 0.1-0.5 mm^2 / 0.5-1 mm^2 / 0.5-1.5 \\ \mbox{mm}^2 \end{array}$

Crimp dimensions inch/AWG: AWG 26 - AWG 20/AWG 20 - AWG 18/AWG 20 - AWG 16 Connector: Uninsulated open barrel connectors Description: For non insulated open

barrel connectors. Life span, cycles: 50,000

Pressmaster AB P.O. Box 3, Industrivägen SE-796 21 Älvdalen, Sweden Tel: +46 (0)251-451 00 info@pressmaster.se www.pressmaster.com