


Product T2258



T2258 is a crimping tool for non insulated tubular connectors 4-16 mm<sup>2</sup>/11-5 AWG.

- Long handles allowing two handed operation for powerful, low effort crimping
- Full cycle crimp mechanism to ensure consistent, reliable crimp
- Ratchet release mechanism to clear miscrimps and obstructions
- Precision eccentric adjustment for consistent performance and ability to calibrate
- · Each tool has a unique serial number for traceability





Die profile

TECHNICAL DATA Length: 304 mm/11.97" Width: 30 mm/1.18" Height: 70 mm/2.76" Weight: 660 gr/1.46 lb Wire size: 4-16 mm<sup>2</sup> / AWG 11-5 Crimp dimensions mm/mm<sup>2</sup>: 4 - 6 mm<sup>2</sup>/10 mm<sup>2</sup>/16 mm<sup>2</sup> Crimp dimensions inch/AWG: AWG 11 - AWG 10/AWG 7/AWG 5 Connector: Uninsulated connectors Description: For uninsulated copper tube connectors.

Life span, cycles: 25,000

Pressmaster AB P.O. Box 3, Industrivägen SE-796 21 Älvdalen, Sweden Tel: +46 (0)251-451 00 info@pressmaster.se www.pressmaster.com