

## **Product**

## T3165A



T3165A is a crimping tool for non insulated tubular connectors 10-70 mm²/7-2/0 AWG.

- Asymmetric dies give optimized crimp result on terminal
- The dies mark the terminal so that they can be inspected for correct use of the tool
- Long handles allowing two handed operation for powerful crimping
- Full cycle crimp mechanism to ensure consistent, reliable crimp
- Ratchet release mechanism to clear miscrimps and obstructions
- Each tool has a unique serial number for traceability





ile Crimp profile

TECHNICAL DATA Length: 492 mm/19.37" Width: 44 mm/1.73" Height: 80 mm/3.15" Weight: 3100 gr/6.84 lb

Wire size: 10-70 mm<sup>2</sup> / AWG 7-2/0 Crimp dimensions mm/mm<sup>2</sup>: 10 mm<sup>2</sup>/16 mm<sup>2</sup>/25 mm<sup>2</sup>/35 mm<sup>2</sup>/50

 $mm^{2}/70 mm^{2}$ 

**Crimp dimensions inch/AWG:** AWG 7/AWG 5/AWG 3/AWG 2/AWG

0/AWG 2/0

Connector: Uninsulated connectors Description: For uninsulated copper tube connectors. Indent crimp Life span, cycles: 50,000